#### (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

## (19) World Intellectual Property Organization International Bureau



# . <u>| 1884 | 1884 | 1884 | 1884 | 1884 | 1884 | 1884 | 1884 | 1884 | 1884 | 1884 | 1884 | 1884 | 1884 | 1884 | 1</u>

#### (43) International Publication Date 17 July 2003 (17.07.2003)

### PCT

# (10) International Publication Number WO 03/058014 A1

(51) International Patent Classification7: 65/10

Collingwood House, 3 Collingwood Street, Newcastle Upon Tyne NE1 1JW (GB).

(21) International Application Number: PCT/GB03/00080

(22) International Filing Date: 13 January 2003 (13.01.2003)

(25) Filing Language:

English

E05B 47/00,

(26) Publication Language:

English

(30) Priority Data: 0200691.4

14 January 2002 (14.01.2002)

(71) Applicants (for all designated States except US): MILA HARDWARE LIMITED [GB/GB]; 1 Brunel Close, Drayton Fields Industrial Estate, Daventry, Northants NN11 5RB (GB). CEDARDELL LIMITED [GB/GB]; (72) Inventors; and


(75) Inventors/Applicants (for US only): WALLIS, Glen, William [GB/GB]; Chestnut Cottage, Wychnor Manor, Wychnor, Burton-On-Trent DE13 8BU (GB). TODD, Rob [GB/GB]; Collingwood House, 3 Collingwood Street, Newcastle Upon Tyne NE1 1JW (GB).

(74) Agents: NEILL, Alastair, William et al.; Appleyard Lees, 15 Clare Road, Halifax HX1 2HY (GB).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE,

[Continued on next page]

(54) Title: LOCKING MECHANISM



A locking mechanism (57) Abstract: is provided which is operable to restrict unauthorised access to a structure such as a house, the locking mechanism being operable to permit external access, by means of at least one remote control device (14) operable from outside the structure, the locking mechanism being arranged to cooperate with at least one internal safety device (17), for example the smoke detector or fire alarm, the locking mechanism being such that if the safety device (17) is activated, this unlocks the locking mechanism to facilitate escape from the structure.